


### PARTS LIST

ITEMS	DESCRIPTION	REF. DATA	REQ.
1	GRID	COPPER NICKEL ALLOY (T11)	3
2	GAGE LEAD	POLYURETHANE WIRE $\phi 0.14 \times 150\text{mm}$	6
3	BASE	EPOXY	3
4	COVER	POLYESTER	1
5	LEAD WIRE	7/0.12 2C DIA 1mm $\times$ 2000mm	3

### SPECIFICATIONS

RESISTANCE :  $120.0\Omega \pm 1.0\Omega$   
 GAGE LENGTH : 1mm  
 GAGE FACTOR : 1.9~2.1  
 TEMPERATURE RANGE :  $-50^\circ\text{C}$  to  $70^\circ\text{C}$



					<b>ミネベア株式会社</b> MINEBEA CO.,LTD. <b>計測機器事業部</b>		単位 UNIT mm 尺度 SCALE FREE	材質 MATERIAL - 表面粗さ SURF.ROUGH. - 熟処理 HEAT TREAT. - 表面処理 FINISH -	作成日 DATE 2014/01/07 品名 DESCRIPTION <b>FR-1A12L15W2MS</b>	
					APPROVED	CHECKED	DRAWN	一般公差 TOL	品番 PART NO. (MODEL NO.)	葉番 SHEET
					D. Inomori	E. MISAZU	S. YAMAMOTO		図番 DRAWING NO. G900494-1	改訂 REV.
符号 MARK	日付 DATE	変更事項 REASON	ECN NO.	担当 ENGINEER	承認 APPROVED					
-	2014/01/07	NEW		YAMAMOTO D. Ina						