



### PARTS LIST

ITEMS	DESCRIPTION	REF. DATA	REQ.
1	GRID	COPPER NICKEL ALLOY (T11)	3
2	GAGE LEAD	POLYURETHANE WIRE $\phi 0.14 \times 500\text{mm}$	6
3	BASE	EPOXY	3
4	COVER	POLYESTER	1
5	LEAD WIRE	7/0.12 2C DIA 1mm	3

### SPECIFICATIONS

RESISTANCE :  $120.0\Omega \pm 1.0\Omega$   
 GAGE LENGTH : 1mm  
 GAGE FACTOR : 1.9~2.1  
 TEMPERATURE RANGE :  $-50^\circ\text{C}$  to  $70^\circ\text{C}$



ミネベア株式会社 MINEBEA CO.,LTD. 計測機器事業部					単位 UNIT mm 尺度 SCALE FREE	材質 MATERIAL	作成日 DATE 2005.12.22
						表面粗さ SURF.ROUGH.	品名 DESCRIPTION FR-1A12L50W05MS
APPROVED D. Inomori					一般公差 TOL 寸法 L 公差 $<L \leq 4$ $\pm 0.1$ $4 < L \leq 16$ $\pm 0.2$ $16 < L \leq 63$ $\pm 0.3$ $63 < L \leq 250$ $\pm 0.5$ $250 < L \leq 1000$ $\pm 0.8$ 角度 DEG $\pm 0.5$	熱処理 HEAT TREAT.	品番 PART NO. (MODEL NO.) 乘番 SHEET
						表面処理 FINISH	図番 DRAWING NO. G900248-1 改訂 REV.
符号 MARK	日付 DATE	ECN NO.	担当 ENGINEER	承認 APPROVED	E.MISAIZU M. HIRAMOTO		