



### PARTS LIST

ITEMS	DESCRIPTION	REF. DATA	REQ.
1	GRID	CUPPER NICKEL ALLOY	3
2	GAGE LEAD	POLYURETHANE WIRE $\phi 0.14 \times 500\text{mm}$	6
3	BASE	EPOXY	3
4	COVER	POLYIMIDE	1
5	LEAD WIRE	7/0.12 2C DIA 1mm $\times$ 2000mm	3

### SPECIFICATIONS

RESISTANCE :  $350.0\ \Omega \pm 3.0\ \Omega$   
 GAGE LENGTH : 1mm  
 GAGE FACTOR : 1.9~2.1  
 TEMPERATURE RANGE :  $-50^{\circ}\text{C}$  to  $70^{\circ}\text{C}$



					<b>ミネベア株式会社</b> MINEBEA CO.,LTD. <b>計測機器事業部</b>		単位 UNIT mm 尺度 SCALE FREE	材質 MATERIAL - 表面粗さ SURF.ROUGH. - 熱処理 HEAT TREAT. - 表面処理 FINISH -	作成日 DATE 2008.12.02 品名 DESCRIPTION <b>FR-1A35L50W2MS</b> 品番 PART NO.(MODEL NO.) - 図番 DRAWING NO. G900324-1	葉番 SHEET - 改訂 REV. A
					APPROVED	CHECKED	DRAWN	一般公差 TOL 寸法 L 公差 <math>L \le 4</math> $\pm 0.1</math>         <math>4 < L \le 16</math> \pm 0.2</math>         <math>16 < L \le 63</math> \pm 0.3</math>         <math>63 < L \le 250</math> \pm 0.5</math>         <math>250 < L \le 1000</math> \pm 0.8</math>         角度 DEG \pm 0.5</math>       $		
A	2009.03.05	KN09-0055	NAGAOKA	D. Ina	D. Inomori	E. MISAIZU	M. HIRAMOTO			
符号 MARK	日付 DATE	ECN NO.	担当 ENGINEER	承認 APPROVED						