



PARTS LIST

ITEMS	DESCRIPTION	REF. DATA	REQ.
1	FOIL	CUPPER NICKEL ALLOY	1
2	GAGE LEAD	POLYURETHANE $\phi 0.14$	2
3	BASE	POLYIMIDE	1
4	COVER	POLYIMIDE	1
5	LEAD WIRE	7/0.12 2C DIA $\phi 1$ mm (WHITE)	1

SPECIFICATIONS

RESISTANCE	:	350.0 Ω \pm 3.0 Ω
GAGE LENGTH	:	3.0 mm
GAGE FACTOR	:	1.9~2.1
TEMPERATURE RANGE	:	-50 $^{\circ}$ C to 70 $^{\circ}$ C



					ミネベア株式会社 MINEBEA CO.,LTD. 計測機器事業部		単位 UNIT mm 尺度 SCALE FREE		材質 MATERIAL -		作成日 DATE 2013/04/15			
					APPROVED D. Inomori		CHECKED E. MISAIZU		DRAWN E. MISAIZU		表面粗さ SURF.ROUGH. -		品名 DESCRIPTION J-3-35T16W3MS	
					一般公差 TOL 寸法 L $<L \leq 4$ ± 0.1 $4 < L \leq 16$ ± 0.2 $16 < L \leq 63$ ± 0.3 $63 < L \leq 250$ ± 0.5 $250 < L \leq 1000$ ± 0.8 角度 DEG ± 0.5		熱処理 HEAT TREAT. -		表面処理 FINISH -		品番 PART NO.(MODEL NO.) -		葉番 SHEET /	
符号 MARK	日付 DATE	変更事項 REASON	ECN NO.	担当 ENGINEER	承認 APPROVED					図番 DRAWING NO. G900468-1		改訂 REV. -		