



# PARTS LIST

ITEMS	DESCRIPTION	REF. DATA	REQ.
1	FOIL	CUPPER NICKEL ALLOY	1
2	GAGE LEAD	POLYURETHANE φ0.14	2
3	BASE	POLYIMIDE	1
4	COVER	POLYIMIDE	1
5	LEAD WIRE	7/0.12 2C DIA φ1mm (RED)	1

# SPECIFICATIONS

RESISTANCE	:	120.0Ω ± 1.0Ω
GAGE LENGTH	:	5.0 mm
GAGE FACTOR	:	1.9~2.1
TEMPERATURE RANGE	:	-50℃ to 70℃



					<b>ミネベア株式会社</b> MINEBEA CO.,LTD. <b>計測機器事業部</b>			単位 UNIT mm 尺度 SCALE FREE		材質 MATERIAL - 表面粗さ SURF.ROUGH. - 熱処理 HEAT TREAT. - 表面処理 FINISH -		作成日 DATE 2013/04/16 品名 DESCRIPTION <b>J-5-12T11W3MS</b>			
					APPROVED D. Inomori			CHECKED E. MISAIZU		DRAWN E. MISAIZU		品番 PART NO. (MODEL NO.) -		葉番 SHEET /	
符号 MARK	日付 DATE	変更事項 REASON	ECN NO.	担当 ENGINEER	承認 APPROVED			一般公差 TOL 寸法 L 公差 <L ≤ 4 ±0.1 4 < L ≤ 16 ±0.2 16 < L ≤ 63 ±0.3 63 < L ≤ 250 ±0.5 250 < L ≤ 1000 ±0.8 角度 DEG ±0.5		図番 DRAWING NO. G900469-1		改訂 REV. -			